Company Name

Costs

Passive Treatment

Vertical Flow Pond

Anoxic Limestone Drain

Anaerobic Wetlands

Manganese Removal Bed

Oxic Limestone Channel

Limestone Bed

BIO Reactor

Passive Subtotal:

Active Treatment

Aerobic Wetlands

Big Mack Leasing

Project

proposed chemical

Site Name Iselin #18

AMD TREAT AMD TREAT MAIN COST FORM

\$0

\$0

\$0

\$0

\$0

\$0

\$0

\$0

\$0



AMOTREAT **Water Quality** Calculated Acidity 1273.87 mg/L Alkalinity 13.00 mg/L Calculate Net Acidity (Acid-Alkalinity) C Enter Net Acidity manually **Net Acidity** 1260.87 mg/L (Hot Acidity) Design Flow gpm 60.00 Typical Flow 30.00 gpm 29.80 mg/L **Total Iron** 3.10 mg/L Aluminum Manganese mg/L 61.30 su pН 5.10 0.00 mg/L Ferric Iron mg/L 29.80 Ferrous Iron Sulfate mg/L 3000.00 mg/L Filtered Fe 0.00 Filtered Al 0.00 mg/L 0.00 mg/L Filtered Mn uS/cm Specific Conductivity 0.00 mg/L **Total Dissolved Solids** 0.00 mg/L Dissolved Oxygen 0.00

0 \$12,387 Caustic Soda \$0 Hydrated Lime \$0 Pebble Quick Lime \$0 Ammonia \$0 Oxidants \$0 Soda Ash \$0 Active Subtotal: **Ancillary Cost** \$6,350 2 0 **Ponds** \$0 Roads \$0 Land Access \$0 Ditching 1 0 \$8,797 **Engineering Cost** \$15,147 **Ancillary Subtotal:** \$25,250 Other Cost (Capital Cost) \$52,784 **Total Capital Cost: Annual Costs** 2 0 \$1,226 Sampling 0 \$10,920 1 Labor 1 0 \$372 Maintenance 1 0 \$1,014 Pumping \$35,675 1 0 **Chemical Cost** \$0 Oxidant Chem Cost 0 \$3,150 Sludge Removal \$0 Other Cost (Annual Cost) \$0 Land Access (Annual Cost) \$52,357 **Total Annual Cost:** 0 1 Other Cost

Total Annual Cost: per 1000 Gal of H2O Treated \$3,318

Project proposed chemical

Site Name <u>Iselin #18</u>

AMD TREAT CAUSTIC SODA



| Z | Opening Screen Water Parameters | Caustic Soda Name propos | sed caustic | | | |
|---|------------------------------------|---|------------------|-----------------------------|--------------------------------------|---------------------------------------|
| | Influent Water | Gallons of Caustic per Year | 83,619.08 | gal/yr | ☐ 17. Automatic Sys | stem? |
| Ī | Parameters that Affect | 2. Gallons of Caustic per Month [| 6,968.25 | gal/mo | 18. PID pH Proportional Control | \$ |
| | Caustic Soda | 3. Gallons of Caustic per Day | 229.09 | gal/day | 19. pH Probe | \$ |
| | Calculated Acidity | ☐ 4. Titration? | | | 20. Chemical Metering Pump | \$ |
| | 1273.87 mg/L Alkalinity | 5. Caustic Titration Volume | The state of the | gal caustic/gal | 21. Water Whee | l Dispenser |
| | 13.00 mg/L | 6. Purity of Caustic Solution | 99.00 | water treated purity of 20% | 22. Dispenser Cost | 4000.00 \$ |
| _ | | 7. Mixing Efficiency of Caustic Solution | 80.00 | caustic solution % | Caustic Sub-To | otals |
| С | Calculate Net Acidity | 8. Tank Cost | 8000 | \$ | 23. Number of Tanks Required | 1 nbi |
| | (Acid-Alkalinity) | 9. Tank Volume | 10000 | gal | 24. Tank Cost | 8,000 \$ |
| C | Enter Net Acidity manually | 10. Delivery Frequency | 12 | times/yr | 25. Automatic System or Wheel | 4,000 \$ |
| | Net Acidity | 11. Valve Unit Cost | 50.00 | \$ | Dispenser Cost 26. Cost of Valves | 100 \$ |
| | (Hot Acidity) 1260.87 mg/L | 12. Number of Valves | 2 | nbr | 27. Feeder Line Cost | 7 \$ |
| | 1200.07 | 13. Feeder Line Length | 20 | ft | 28. Labor Cost | 280 \$ |
| | Design Flow | 14. Feeder Line Unit Cost | 0.35 | \$/ft | | · · · · · · · · · · · · · · · · · · · |
| | 60.00 gpm Typical Flow | 15. Installation of System Unit Cost | 35.00 | \$/hr | 29. Total Capital Cost | 12,387 \$ |
| | 30.00 gpm | 16. Installation Hours | 8 | hours | | |
| | Total Iron 29.80 mg/L | | | | | |
| | Aluminum | | | | Record Number 1 | of 1 |
| | 3.10 mg/L | | | | | |
| | Manganese 61.30 mg/L | | | | | |

Project proposed chemical

Site Name Iselin #18

AMD TREAT

PONDS



| | , 6,1,56 | HMUTIRE | =14 1 |
|-----------------------------------|--|--|------------------|
| Pond Name proposed tre | atment ponds | • | |
| | Pond Design Based On: | 23. Revegetation Cost | 1500.00 \$/acre |
| | Retention Time | 24. Number of Ponds for this Design | 3 number |
| | 1. Desired Retention Time 18.0 hours | 25. Cost of Baffles | 0 \$ |
| | 2. Include Sludge Removal? 3. Sludge Removal Frequency times/year | Calculated Pond Dimension | ns per Pond |
| ☑ Opening Screen Water Parameters | 4. Titration? | 26. Length at Top of Freeboard | 75 ft |
| water Parameters | gal sludge/ | 27. Width at Top of Freeboard | 39 ft |
| Influent Water | 5. Sludge Rate gal H2O | 28. Freeboard Volume | 422 yd3 |
| Parameters | 6. Percent Solids % | 29. Water Volume | 320 yd3 |
| that Affect Ponds | 7.Sludge Density lbs./gal | 30. Estimated Annual Sludge | 0 yd3/yr |
| Calculated Acidity | C Pond Size | 31. Volume of Sludge | 0 yd3/ remova |
| 1273.87 mg/L | 8. Pond Length at Top of Freeboard ft | per Removal 32. Excavation Volume | 0.19 acre ft |
| Alkalinity | 9. Pond Width at Top of Freeboard ft | 32. Excavation Volume | 320 yd3 |
| 13.00 mg/L | | 34. Clear and Grub Area | 0.10 acres |
| | Run Rise | 35. Liner Area | 410 yd2 |
| Calculate Net Acidity | 10. Slope Ratio of Pond Sides 2.0 : 1 | 36. Calculated Retention Time | 18 hours |
| (Acid-Alkalinity) | 11. Freeboard Depth 1.0 ft | | |
| C Enter Net Acidity | 12. Water Depth 6.0 ft | Ponds Sub-Tot | |
| manually | 13. Excavation Unit Cost 2.50 \$/yd3 | 37. Excavation Cost | 3,160 \$ |
| Net Acidity (Hot Acidity) | 14 Total Length of Effluent | 38. Pipe Cost | 158 \$ |
| 1260.87 mg/L | / Influent Pipe | 39. Liner Cost | 1,358 \$ |
| 1200.07 mg/L | 15. Unit Cost of Pipe 7.90 \$/ft | 40. Clearing and Grubbing Cost | 0 \$ |
| Design Flow | Liner Cost | 41. Revegetation Cost | 153 \$ |
| 60.00 gpm | C No Liner | 42. Baffle Cost | 0 \$ |
| Typical Flow | Clay Liner 16. Clay Liner Unit Cost 4.50 \$/yd3 | | |
| 30,00 gpm | 17. Thickness of Clay Liner 1.0 ft | ☑ 43. Estimated Cost | 4,830 \$ |
| 29.80 mg/L | C Synthetic Liner | | |
| Aluminum | 18. Synthetic Liner Unit Cost \$/yd2 | | |
| 3.10 mg/L | ☐ 19. Clearing and Grubbing? | The Recommended Minimum Const Cost of Building a Pond is \$ 5,000 | |
| Manganese 61.30 mg/L | 20. Land Multiplier ratio | 45. Recommended Minimum Cost | 5,000 \$ |
| | 21. Clear/Grub Acres acres | J. Neconimended willimidin cost | |
| Record Number | 22. Clear and Grub Unit Cost \$/acre | 46. Total Cost | 5,000 \$ |
| 1 of 2 | 機能を記述する Wade | | |

Project proposed chemical

Site Name Iselin #18

AMD TREAT



PONDS

| Pond Name Sludge drying b | asin | | |
|--|---|--|-----------------|
| i | Pond Design Based On: | 23. Revegetation Cost 150 | 0.00 \$/acre |
| | C Retention Time | 24. Number of Ponds for this Design | 1 numbe |
| | Desired Retention Time hours | 25. Cost of Baffles | 0 \$ |
| | 2. Include Sludge Removal? | | |
| | 3. Sludge Removal Frequency times/year | Calculated Pond Dimensions per | Pond |
| ☑ Opening Screen Water Parameters | ☐ 4. Titration? | 26. Length at Top of Freeboard | 75 ft |
| | 5. Sludge Rate gal sludge/ | 27. Width at Top of Freeboard | 50 ft |
| Influent Water | 6. Percent Solids % | 28. Freeboard Volume | 644 yd3 |
| Parameters that Affect | 7. Sludge Density Ibs./gal | 29. Water Volume | 514 yd3 |
| Ponds | 7. Studge Delisity 105./gal | 30. Estimated Annual Sludge | 0 yd3/yr |
| Calculated Acidity 1273.87 mg/L | € Pond Size | 31. Volume of Sludge per Removal | 0 yd3/ remov |
| Alkalinity | 8. Pond Length at Top of Freeboard 75.000 ft | | 0.31 acre ft |
| 13.00 mg/L | 9. Pond Width at Top of Freeboard 50.000 ft | 33. Excavation Volume | 514 yd3 |
| | Run Rise | 34. Clear and Grub Area | .12 acres |
| Calculate Net | 10. Slope Ratio of Pond Sides 2.0 : 1 | 35. Liner Area | 0 yd2 |
| Acidity (Acid-Alkalinity) | 11. Freeboard Depth 1.0 ft | 36. Calculated Retention Time | 28 hours |
| C Enter Net Acidity 12. Water Depth 8.0 ft | | Ponds Sub-Totals per Pond | |
| manually | | 37. Excavation Cost 1 | ,285 \$ |
| Net Acidity (Hot Acidity) | 13. Excavation Unit Cost 2.50 \$/yd3 14. Total Length of Effluent 6.000 ft | 38. Pipe Cost | 0 \$ |
| 1260.87 mg/L | / Influent Pipe 0.00 ft | 39. Liner Cost | 0 \$ |
| 1200.07 | 15. Unit Cost of Pipe 0.00 \$/ft | 40. Clearing and Grubbing Cost | 0 \$ |
| Design Flow | © No Liner | 41. Revegetation Cost | 64 \$ |
| 60.00 gpm | C Clay Liner | 42. Baffle Cost | 0 \$ |
| Typical Flow 16. Clay Liner Unit Cost \$/yd3 | | | |
| Total Iron | 17. Thickness of Clay Liner ft | 43. Estimated Cost | ,350 \$ |
| 29.80 mg/L | C Synthetic Liner | | |
| Aluminum | 18. Synthetic Liner Unit Cost \$/yd2 | 44. Accept Minimum Pond C | ost? |
| 3.10 mg/L Manganese | ☐ 19. Clearing and Grubbing? | The Recommended Minimum Construction Cost of Building a Pond is \$ 5,000 | |
| 61.30 mg/L | O 20. Land Multiplier ratio | | \$ |
| | () 21. Clear/Grub Acres acres | 5. Recommended Minimum Cost | |
| Record Number 2 of 2 | 22. Clear and Grub Unit Cost \$/acre | 46. Total Cost | ,350 \$ |

Project proposed chemical

Site Name Iselin #18

AMD TREAT ENGINEERING COST

1. Capital Cost * 43,987 \$

• 2. Per Cent of Capital Cost 20.00 %

• 3. Actual Engineering Cost \$

4. Total Engineering Cost 8,797 \$

* Total Capital Cost minus Engineering and Land Access Capital Cost Printed on 03/24/2008



Project proposed chemical

Site Name <u>Iselin #18</u>

AMD TREAT OTHER COST



| Oher Cost Name | | | IAMDII KEIA | |
|---------------------------------|-----------------------------|----------------|--------------------------|--|
| A. Description of Item | B. Unit Cost Per Item | C. Quantity | D. Total Item Cost | E. Capital Cost Annual Cost |
| construct/install power line | 15,000.00 | 1 | 15,000 | CAnnual Cost |
| 2. pump | 8,000.00 | 1 | 8,000 | Capital CostC Annual Cost |
| 3. building 15'X15' @ \$10/sqft | 2,250.00 | 1 | 2,250 | CApital Cost CAnnual Cost |
| 4. | 0.00 | 0 | 0 | Capital Cost Annual Cost |
| 5. | 0.00 | 0 | 0 | C∵Annual Cost |
| 6. | 0.00 | 0 | 0 | ← Capital Cost ← Annual Cost |
| 7. | 0.00 | 0 | 0 | C Capikal Cost C Annual Cost |
| 8. | 0.00 | 0 | 0 | Capital Cost Annual Cost |
| 9. | 0.00 | 0 | 0 | Capital Cost C Annual Cost |
| 10. | 0.00 | 0 | 0 | Capital Cost Annual Cost |
| 11. | 0.00 | 0 | 0 | C Capital Cost |
| 12. | 0.00 | 0 | 0 | Capital Cost C Annual Cost |
| 13. | 0.00 | 0 | 0 | Capital Cost Annual Cost |
| 14. | 0.00 | 0 | 0 | Capital Cost Annual Cost |
| 15. | 0.00 | 0 | 0 | Capital Cost Annual Cost |

| Curent Capital Cost | 25,250 \$ |
|---------------------|-------------|
| Current Annual Cost | C \$ |

| Total Capital Cost | 25,250 \$ |
|--------------------|-----------|
| Total Annual Cost | 0 \$ |

Project proposed chemical

Site Name <u>Iselin #18</u>

final - monthly

Sampling Name

AMD TREAT

SAMPLING



| F Estimate Sampling Cost | | |
|--------------------------------|-------------|--------------|
| 1. Unit Labor Cost | 35.00 | \$/hr |
| 2. Collection Time per Sample | 0.25 | hours/sample |
| 3. Travel Time | 1.00 | hr |
| 4. Sample Frequency | 1.00 | samples/mo |
| 5. Lab Cost Per Sample | 25.00 | \$/sample |
| 6. Number of Sample Points | 1 | points |
| C Enter Established Annual Sar | npling Cost | |
| 7. Actual Annual Sampling Cost | | \$ |

Sampling Sub-Totals

- 8. Yearly Sample Analysis Cost 300 \$
 - 9. Yearly Travel Cost 420 \$
 - 10. Yearly Collection Cost 105 \$

11. Sampling Cost 825 \$

Project proposed chemical

Site Name Iselin #18

AMD TREAT SAMPLING



| Compline Name | quarterly - raw, upstr, downstr |
|---------------|---|
| Samound Name | LOUATIENV - TAW. DOSIL. DOWNSH |
| g | qualitating turning appears are trained |
| | <u></u> |

| Estimate | Sampling Cost | | | |
|--|--------------------|-------|--------------|--|
| | 1. Unit Labor Cost | 35.00 | \$/hr | |
| Collection | Time per Sample | 0.25 | hours/sample | |
| | 3. Travel Time | 0.00 | hr | |
| 4. 9 | Sample Frequency | 0.33 | samples/mo | |
| 5. Lat | Cost Per Sample | 25.00 | \$/sample | |
| 6. Numbe | r of Sample Points | 3 | points | |
| C Enter Established Annual Sampling Cost | | | | |
| 7. Actual Ann | ual Sampling Cost | | \$ | |

Sampling Sub-Totals

- 8. Yearly Sample Analysis Cost 297 \$
 - 9. Yearly Travel Cost 0 \$
 - 10. Yearly Collection Cost 104 \$

11. Sampling Cost 401 \$

Labor Name

Project proposed chemical

Site Name Iselin #18

weekly labor

AMD TREAT

LABOR



| © Estimate Labor Cost | |
|----------------------------------|---------------|
| 1. Site Visits per Week | 3.00 |
| 2. Site Labor Time per Visit | 1.00 hours |
| 3. Travel Time per Visit | 1.00 hours |
| 4. Unit Labor Cost | 35.00 \$/hour |
| C Enter Established Annual Labor | Cost |
| 5. Actual Annual Labor Cost | \$ |
| | |

6. Total Cost 10,920 \$

Project proposed chemical

Site Name Iselin #18

AMD TREAT

MAINTANENCE

| Estimate Maintenance Cost | |
|---|-----------------|
| 1. Percent of Active Cost | 3.00 % |
| 2. Percent of Passive Cost | 1.00 % |
| 3. Percent of Ancillary Cost * | 0.00 % |
| 4. Percent of Other Capital Cost | 0.00 % |
| C Enter Established Annual Mainter | nance Cost |
| 5. Annual Maintenance Cost | \$ |
| Mainter | ance Sub-Totals |
| 6 Total Maintenance Active Cost | 372 \$ |
| 7. Total Maintenance Passive Cost | 0 \$ |
| 8. Total Maintenance Ancillary Cost | 0 \$ |
| 9. Total Maintenance Other Capital Cost | 0 \$ |
| 10. Total Maintenance Cost | 372 \$ |



^{*} Ancillary Cost does int include Cost for Land Access and Engineering Cost

Project proposed chemical

Site Name Iselin #18

AMD TREAT PUMPING



Pumping Name

| Estimated Electricity Cost for | Pumping | C Estimated Fuel Cost for Pumping |
|---------------------------------|----------------|-----------------------------------|
| 1. Pump Rate | 30.00 gal/min | 12. Fuel Rate gal/hr |
| 2. Total Pump Head | 70.00 feet | 13. Fuel Cost \$/gal |
| 3. Electricity Cost | 0.09 \$/kwhour | 14. Hours Per Day hours |
| 4. Hours Per Day | 24.00 hours | 15. Days Per Year days |
| 5. Days Per Year | 365 days | 16. Pump Maintenance Cost %** |
| 6. Pump Efficiency | 75.00 % | 17. Estimated Annual Fuel Cost \$ |
| 7. Motor Efficiency | 85.00 % | 18. Estimated Maintenance Cost \$ |
| 8. Pump Maintenance Cost | 18.00 %* | ** Percent of Annual Fuel Cost |
| 9. Est. Annual Electricity Cost | 859 \$ | 1 order of Allindar 1 doi oost |
| 10. Est. Maintenance Cost | 155 \$ | |
| * Percent of Annual Electricity | y Cost | |
| C Enter Established Annual Pum | ping Cost | |
| 11. Actual Annual Pumping Cost | \$ | |

19. Total Pumping Cost 1,014 \$

Project proposed chemical

Site Name | Iselin #18

AMD TREAT CHEMICAL COST



Chemical Cost Name: A. Hydrated Lime? E. Anhydrous Ammonia? Opening Screen 21. Titration? Water Parameters 1 Titration? lbs of ammonia lbs of hydrated 22. AmmoniaTitration Amount 2. Hydrated Lime Titration Amount / gal H2O lime / gal of H2O Influent Water 23. Ammonia Purity % 3. Hydrated Lime Purity **Parameters** that Affect % 24. Mixing Efficiency of Ammonia 4. Mixing Efficiency of Hydrated Lime % **Chemical Cost** Non-Bulk Delivery 5. Hydrated Lime Unit Cost \$/lb Calculated Acidity 25. Ammonia Non-Bulk Unit Cost \$/lb 1273.87 mg/L B. Pebble Quick Lime? Bulk Delivery Alkalinity 6. Titration? 26. Ammonia Bulk Unit Cost \$/lb 13.00 mg/L lbs of Pebble 7. Pebble Lime Titration Amount Lime / gal of H2O F. Soda Ash? 8. Pebble Lime Purity Calculate Net 27. Titration? Acidity 9. Mixing Efficiency of Pebble Lime % lbs of soda ash 28 Soda Ash Titration Amount (Acid-Alkalinity) gal of H2O (Delivered in Bags Enter Net Acidity 29. Soda Ash Purity % S manually 10. Pebble Lime Bag Unit Cost \$/lb 30. Mixing Efficiency of Soda Ash % Net Acidity Bulk Delivery (Hot Acidity) \$/lb 11. Pebble Lime Bulk Unit Cost 31 Soda Ash Unit Cost \$/lb 1260.87 mg/L C. Caustic Soda? G. Known Chemical Cost? ✓ 12. Titration? 32. Known Annual Chemical Cost Design Flow gal ofcaustic **Annual Amount of** 13. Caustic Titration Amount .0014480000 60.00 gpm gal H2O **Chemical Cost Sub-Totals Chemicals Consumed** purity of 20% Typical Flow 14. Caustic Purity lbs 33. Total Hydrated Lime Cost ol \$ ol caustic solution 30.00 gpm 15. Mixing Efficiency of Caustic 80.00 \$ ibs 34. Total Pebble Lime Cost Total Iron Non-Bulk Delivery Total Caustic Soda Cost 35.675 \$ 28,540 gals 29.80 mg/L \$/gal 16. Caustic Non-Bulk Unit Cost Aluminum 36. Total Limestone Cost \$ tons 0 Bulk Delivery 3.10 mg/L 37. Total Anhydrous Ammonia Cost \$ lbs O 0 1.25 \$/gal 17. Caustic Bulk Unit Cost Manganese 38. Total Soda Ash Cost lbs 0 61.30 mg/L C D. Limestone? 39. Total Known Chemical Cost \$ 18. Limestone Purity 40. Selected Chemical: CAUSTIC SODA Record Number 19. Limestone Efficiency Annual Chemical Cost \$ 35,675 20 Limestone Unit Cost 1 of 1 \$/ton

Project proposed chemical

Site Name <u>Iselin #18</u>

AMD TREAT



| ☐ Opening Screen Water Parameters | Sludge Removal Name | GMD. | | |
|--|------------------------------------|---|--|--|
| Influent Water Parameters that Affect | 1. Select One | Selection for Method of Removing Sludge | 14. Iron Conce | |
| Sludge Removal | Sludge Removal | 15. Manganese Conc | | |
| Calculated Acidity 1273.87 mg/L | 2. Sludge Remova | al Unit Cost 0.05 \$/gal | 16. Aluminum Conce | |
| Alkalinity 13.00 mg/L | C Sludge Removal 3. Vacuum Truc | | 17. Total Miscellaneous Conce | |
| | 4. Mobiliz | zation Cost \$ | 19. Sludge | |
| Calculate Net Acidity | | to be Used hr by Mechanical Excavation | □ 20 T | |
| (Acid-Alkalinity) C Enter Net Acidity manually | 6. Mechanical Excavation | | 21. Gal. of Sludge per Gal of Wate | |
| Net Acidity (Hot Acidity) | 1 | zation Cost \$ to be Used hr | 22. Estimated Sludge | |
| 1260.87 mg/L | | by Lagoon Cleaner | Cost | |
| Design Flow | 9. Lagoon Cleanin | | 23. Removal by \$ pe | |
| 60.00 gpm Typical Flow 30.00 gpm | 10. Mobili | zation Cost \$ to be Used hr | 24. Removal by Vacuu 25. Removal by Mechanical Ex | |
| Total Iron | C Actual Sludge R | | 26. Removal by Lagoon 27. Actual Sludge Remo | |
| 25 mg/L Aluminum 4 mg/L | 12. Actual Sludge Re | emoval Cost \$ | Sludge Re | |
| Manganese 50 mg/L | 13. Off Site Di | sposal Cost 0.00 \$ | 28. Currently Selected Remo | |

| 14. Iron Concentration | 29.80 mg/L | | | | | |
|---|--------------|--|--|--|--|--|
| 15. Manganese Concentration | 61.30 mg/L | | | | | |
| 16. Aluminum Concentration | 3.10 mg/L | | | | | |
| 17. Total Miscellaneous Concentration | 0 mg/L | | | | | |
| 18. Percent Solids | 1.00 % | | | | | |
| 19. Sludge Density | 8.33 lbs/gal | | | | | |
| ☐ 20 Titration? | | | | | | |
| 21. Gal. of Sludge per Gal of Water Treated | gal | | | | | |
| 22. Estimated Sludge Volume | 311 yd3/yr | | | | | |
| Cost for Sludge Removal Types | | | | | | |
| 23. Removal by \$ per Gallon | 3,150 \$ | | | | | |
| 24. Removal by Vacuum Truck | 0 \$ | | | | | |
| 25. Removal by Mechanical Excavation | 0 \$ | | | | | |
| 26. Removal by Lagoon Cleaner | 0 \$ | | | | | |
| 27. Actual Sludge Removal Cost | 0 \$ | | | | | |
| Sludge Removal Sub-Totals | | | | | | |
| 28. Currently Selected Removal Cost Plus Off Site Disposal Cost | 3,150 \$ | | | | | |

Project proposed chemical

Site Name Iselin #18

AMD TREAT RECAPITIZALITION COST



AMDTREAT

Calculation Period 75 yrs Inflation Rate 3.10 % Net Return Rate 6.00 %

Recapitizalition Name Chemical - bond

| A. | В | С | D | E | F | G |
|----------------------------|-----------------------|----------|--------------------|---------------|----------------------|-------------|
| Description of Item | Unit Cost Per Item | Quantity | Total Item Cost | Life Cycle | Number of Periods | Total PV |
| replace caustic components | 12,387 | 1 | 12,387 | 25 | 3 | 10,833 |
| 2. replace pump | 8,000 | 1 | 8,000 | 5 | 15 | 47,057 |
| 3. replace ponds | 6,350 | 1 | 6,350 | 25 | 3 | 5,553 |
| 4. | 0 | 0 | 0 | 0 | 0 | 0 |
| 5. | 0 | 0 | . 0 | 0 | . 0 | Q. |
| 6. | 0 | 0 | 0 | 0 | 0 | 0 |
| 7. | 0 | 0 | 0 | 0 | 0 | 0 |
| 8. | 0 | 0 | 0 | 0 | 0 | 0 |
| 9. | 0 | 0 | 0 | 0 | 0 | 0 |
| 10. | 0 | 0 | 0 | 0 | 0 | 0 |
| 11. | 0 | 0 | 0 | 0 | 0 | 0 |
| 12. | 0 | 0 | 0 | 0 | 0 | 0 |
| 13. | 0 | 0 | 0 | 0 | 0 | 0 |
| 14. | 0 | 0 | 0 | 0 | 0 | 0 |
| 15. | 0 | 0 | 0 | 0 | 0 | 0 |
| 16. | 0 | 0 | 0 | .0 | 0 | 0 |
| 17. | 0 | 0 | 0 | 0 | 0 | 0 |
| 18. | 0 | 0 | 0 | 0 | 0 | 0 |
| 19. | 0 | 0 | 0 | 0 | 0 | 0 |
| 20. | 0 | 0 | 0 | 0 | 0 | 0 |

Total Capital Cost 26,737 PV Grand Total 63,443 \$