



DESIGN AND CONSTRUCTION: CONTRACTOR SHALL FIELD VERIFY DEPTH OF ALL EXITING UTILITIES SHOWN OR NOT SHOWN ON

- THE MINIM IM SEPARATION DISTANCE FROM EXISTING SUBSURFACE LITH THES SHALL NOT BE LESS. 2. THE MINIMUM SEPARATION DISTANCE FROM EXISTING SUBSURFACE UTILITIES SHALL NOT BE LESS THAN 10 FEET AS MEASURED FROM THE OUTSIDE EDGE OF THE UTILITY TO OUTSIDE OF PROPOSED PIPELINE.

  3. DESIGNED IN ACCORDANCE WITH CFR 49 195 & ASME B31.4

  4. CROSSING PIPE SPECIFICATION:

  HDD HORZ. LENGTH (L=):2645'
  HDD PIPE LENGTH (L=):2645'
  20' x 0.456' W.T., X-65, API5L, PSL2, ERW, BFW
  COATING: 14-16 MILS FBE WITH 30-35 MIL ARO (POWERCRETE R95)

-CL (16.5' - 21.0')

-SC (21.0' - 30.0') -COMPLETION DEPTH EL. 709'

- 5. INTERNAL DESIGN PRESSURE 1480 PSIG (SEAM FACTOR 1.0, DESIGN FACTOR 0.50). INSTALLATION METHOD: HORIZONTAL DIRECTIONAL DRILL (HDD)
- PIPELINE WARNING MARKERS SHALL BE INSTALLED ON BOTH SIDES OF ALL ROAD, RAILWAY, AND STREAM CROSSINGS

- STREAM CROSSINGS.

  8. CARRIER PIPE NOT ENCASED.

  9. PIPE / AMBIENT TEMPERATURE MUST BE NO LESS THAN 30°F DURING PULLBACK WITHOUT PRIOR WRITTEN APPROVAL FROM THE ENGINEER.

  10. CONDUCT 4-HOUR PRE-INSTALLATION HYDROTEST OF HDD PIPE STRING TO MINIMUM 1850 PSIG.

  11. SEE SUNOCO PENNSYLVANIA PIPELINE PROJECT ESRI WEBMAP FOR ACCESS ROAD ALIGNMENT.
- 12. SUNOCO PIPELINE, L.P.'S HORIZONTAL DIRECTIONAL DRILL INADVERTENT RETURN CONTINGENCY PLAN
- WILL BE IMPLEMENTED AT ALL TIMES.
  SUNOCO PIPELINE, L.P.'S EROSION AND SEDIMENTATION CONTROL PLAN WILL BE IMPLEMENTED AT ALL

NOTE: REFER TO TEST BORING LOG <u>S2-0081</u> FOR COMPLETE SOIL MATERIAL DESCRIPTION REF. DRAWING REVISIONS NOTES 1. ALL COORDINATES SHOWN ARE IN LATITUDE AND LONGITUDE. ALL MSL ELEVATIONS ARE NAD83 ES-4.27 TO ES-4.29 EROSION & SEDIMENT PLAN EP2 REVISED PER PADEP COMMENTS RECEIVED 09-06-16 MRS 09/30/16 RMB 09/30/16 AAW 09/30/16 1. ALL COORDINATES SHOWN ARE IN LATITUDE AND LONGITUDE. ALL MSL ELEVATIONS ARE NADB3
2. STATIONING IS BASED ON HORIZONTAL DISTANCES.
3. ROONEY ENGINEERING, INC. AND SUNDCO PIPELINE, IP ARE NOT RESPONSIBLE FOR LOCATION
OF FOREIGN UTILITIES SHOWN IN PLOT PLAN OR PROFILE. THE INFORMATION SHOWN HEREON IS
FURNISHED WITHOUT LIABILITY ON THE PART OF ROONEY ENGINEERING, INC. AND SUNDCO PIPELINE,
IP, FOR ANY DAMAGES RESULTING FROM ERRORS OR OMISSIONS THEREIN.
4. CONTRACTOR IS RESPONSIBLE FOR LOCATING ALL UTILITIES. CONTACT ONE CALL AT 811 PRIOR TO
DIGGING. TO SHEET 17 EP1 REVISED PER PADEP COMMENTS DLM 05/09/16 RMB 05/09/16 AAW 05/09/16 DLM 11/13/15 RMB 11/13/15 AAW 11/13/15 C ADDED GEOTECH INFO/DESIGN ADJUSTMENT MRS 10/27/15 RMB 10/27/15 AAW 10/27/15 B ISSUED FOR BID MRS 07/31/15 RMB 07/31/15 AAW 07/31/15 DIGGING.
5. SUNOCO EMERGENCY HOTLINE NUMBER IS #1-800-786-7440. A ISSUED FOR FOR REVIEW KB 04/15/15 RMB 04/15/15 AAW 04/15/15 BY DATE CHK DATE APP DATE DWG NO DESCRIPTION NO. DESCRIPTION



20-INCH HORIZONTAL DIRECTIONAL DRILL WOODBINE DRIVE PENNSYLVANIA PIPELINE PROJECT

SUNOCO PIPELINE, L.P.

TETRA TECH ROONEY (303) 792-5911 SCALE: 1"=250'

DWG. NO: PA-DA-0063.0000-RD