



12. SUNOCO PIPELINE, L.P.'S HORIZONTAL DIRECTIONAL DRILL INADVERTENT RETURN CONTINGENCY PLAN WILL BE IMPLEMENTED AT ALL TIMES. SUNOCO PIPELINE, L.P.'S EROSION AND SEDIMENTATION CONTROL PLAN WILL BE IMPLEMENTED AT ALL

- THE MINIMUM SEPARATION DISTANCE FROM EXISTING SUBSURFACE UTILITIES SHALL NOT BE LESS. THAN 10 FEET AS MEASURED FROM THE OUTSIDE EDGE OF THE UTILITY TO OUTSIDE OF PROPOSED
- PIPEI INF DESIGNED IN ACCORDANCE WITH CFR 49 195 & ASME B31.4

DESIGNED IN ACCORDANCE WITH CFR 49 195 & ASME B31.4 CROSSING PIPE SPECIFICATION: HDD HORZ, LENGTH (L=):2800' HDD PIPE LENGTH (S=):2819' 16" x 0.438" W.T., X-70, APISL, PSL2, ERW, BFW COATING: 14-16 MILS FBE WITH 30-35 MIL ARO (POWERCRETE R95)

-WEATHERED GNEISS

(23.0' - 24.0')

-COMPLETION

DEPTH EL. 411'

NOTE: REFER TO TEST BORING LOG S3-0280 FOR COMPLETE SOIL MATERIAL DESCRIPTION NOTES REF. DRAWING REVISIONS ALL COORDINATES SHOWN ARE IN LATITUDE AND LONGITUDE. ALL MSL ELEVATIONS ARE NAD83
2. STATIONING IS BASED ON HORIZONTAL DISTANCES.
3. ROONEY ENGINEERING, INC. AND SUNDOO PIPELINE, LP ARE NOT RESPONSIBLE FOR LOCATION
OF FOREIGN UTILITIES SHOWN IN PLOT PLAN OR PROFILE. THE INFORMATION SHOWN HEREON IS
FURNISHED WITHOUT LIABILITY ON THE PART OF ROONEY ENGINEERING, INC. AND SUNOCO PIPELINE,
LP, FOR ANY DAMAGES RESULTING FROM ERRORS OR OMISSIONS THEREIN. O ES-6.26 EROSION & SEDIMENT PLAN ES-6.24 TO SHEET 15 AFRIAL SITE PLAN EP1 REVISED PER PADEP COMMENTS MRS 05/09/16 RMB 05/09/16 AAW 05/09/16 4. CONTRACTOR IS RESPONSIBLE FOR LOCATING ALL UTILITIES. CONTACT ONE CALL AT 811 PRIOR TO MRS 02/26/16 RMB 02/26/16 AAW 02/26/16 5. SUNOCO EMERGENCY HOTLINE NUMBER IS #1-800-786-7440. 0 ISSUED FOR CONSTRUCTION MRS 02/19/16 RMB 02/19/16 AAW 02/19/16 BY DATE CHK DATE APP DATE DESCRIPTION DWG NO DESCRIPTION



(303) 792-5911

TETRA TECH ROONEY

PIPELINE WARNING MARKERS SHALL BE INSTALLED ON BOTH SIDES OF ALL ROAD, RAILWAY, AND STREAM CROSSINGS.

9. PIPE / AMBIENT TEMPERATURE MUST BE NO LESS THAN 30°F DURING PULLBACK WITHOUT PRIOR

WRITTEN APPROVAL FROM THE ENGINEER.
CONDUCT 4-HOUR PRE-INSTALLATION HYDROTEST OF HDD PIPE STRING TO MINIMUM 1850 PSIG.
SEE SUNOCO PENNSYLVANIA PIPELINE PROJECT ESRI WEBMAP FOR ACCESS ROAD ALIGNMENT.

CARRIER PIPE NOT ENCASED

16-INCH HORIZONTAL DIRECTIONAL DRILL PENNSYLVANIA TURNPIKE 76 PENNSYLVANIA PIPELINE PROJECT

SUNOCO PIPELINE, L.P.

(31.4' - 32.0')

-COMPLETION

GEOTECH SB-06

-TOPSOIL (0' - 0.3')

-SM (0.3' - 30.0')

DEPTH EL. 404'

-COMPLETION

-GROUNDWATER (23.0')

-NG EL. 434'

DEPTH EL. 394'

-FRACTURED GNEISS (32.0' - 37.0')

DWG. NO: PA-CH-0088.0000-RD-16 SCALE: 1"=300"