SAFETY DATA SHEET



1. Identification

Product identifier SUPER GEL-X®

Other means of identification None.

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO, an MTI Company Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store in accordance with local/regional/national regulations.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 6.96% of the mixture consists of component(s) of unknown acute oral toxicity. 7.99% of the

mixture consists of component(s) of unknown acute dermal toxicity. 7.99% of the mixture consists

of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Material name: SUPER GEL-X®

4786 Version #: 41 Revision date: 19-August-2020 Issue date: 10-October-2013

Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	5 - < 10
CRISTOBALITE		14464-46-1	1 - < 3
Other components below reportable levels			90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Occupational Exposure Limits for constituents are listed in Section 8.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Prolonged exposure may cause chronic effects.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the

Environmental precautions

No special environmental precautions required. Prevent discharge of larger quantity to drain.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Material name: SUPER GEL-X®

Components	Туре	Value	Form
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Туре	Value	Form
QUARTZ (SIO2) (CAS 4808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Constituents	Туре	Value	Form
NERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
JS. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	Form
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	Form
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values No	biological exposure limits noted for the ing	radiant(s)	

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines**

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Applicable for industrial settings only. Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Applicable for industrial settings only. Wear appropriate chemical resistant gloves. Hand protection Applicable for industrial settings only. Use of an impervious apron is recommended. Other Respiratory protection Applicable for industrial settings only. Use a particulate filter respirator for particulate

concentrations exceeding the Occupational Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Observe any medical surveillance requirements. Always observe good personal hygiene considerations

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state Solid. **Form**

Color Not available. Not available. Odor Not applicable. **Odor threshold**

8.5 - 11рH

Melting point/freezing point > 842 °F (> 450 °C) / Not applicable.

Initial boiling point and boiling Not applicable.

range

Material name: SUPER GEL-X®

Flash point Not applicable.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure
Vapor density

Relative density

Not applicable.

2.6 g/cm³

Solubility(ies)

Solubility (water) < 0.9 mg/l

Partition coefficient (n-octanol/water)

Not applicable.

Not applicable.

Auto-ignition temperature Not applicable.

Decomposition temperature > 932 °F (> 500 °C)

Viscosity Not applicable.

Other information

Viscosity temperature

Bulk density 0.9 - 1.4 g/cm³ **Explosive limit** Not applicable. Not explosive. **Explosive properties Explosivity** Not applicable. Not applicable. Flame extension **Flammability** Not applicable. Flammability (flash back) Not applicable. Not applicable. Flammability (Heat of

combustion)

Flammability (Train fire)

Flammability class

Flash point class

Molecular formula

Molecular weight

Oxidizing properties

Not applicable.

Not applicable.

Not applicable.

Not oxidizing.

Percent volatile 0 % pH in aqueous solution 8.5 - 11

Specific gravity Not applicable.

VOC CARB 0 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidKeep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Material name: SUPER GEL-X® SDS US

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Not known. **Acute toxicity**

Product Species Test Results

Bentonite

Acute

Inhalation

Dust

Rat > 5.27 mg/l, 4 hr OECD 436 LC50

Oral Dust

LD50 Rat > 2000 mg/kg OECD 425

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (SIO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (SIO2) (CAS 14808-60-7) **US. National Toxicology Program (NTP) Report on Carcinogens**

QUARTZ (SIO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -Not classified.

single exposure

Material name: SUPER GEL-X® SDS US

4786 Version #: 41 Revision date: 19-August-2020 Issue date: 10-October-2013

Specific target organ toxicity repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results Bentonite Aquatic Algae EC50 Freshwater algae > 100 mg/l, 72 hours Crustacea EC50 Coon stripe shrimp (Pandalus danae) 24.8 mg/l, 96 hours Daphnia > 100 mg/l, 48 hours Dungeness or edible crab (Cancer 81.6 mg/l, 96 hours magister)

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

LC50

Other adverse effects

Fish

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Dispose of contents/container in accordance with local/regional/national/international regulations.

16000 mg/l, 96 hours

2800 - 3200 mg/l, 24 hours

Local disposal regulations

Dispose in accordance with all applicable regulations.

Freshwater fish

Marine water fish

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Material name: SUPER GEL-X® SDS US

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (SIO2) (CAS 14808-60-7) Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Total food additive Direct food additive Administration (FDA) GRAS food additive

US state regulations

California Proposition 65



WARNING: This product can expose you to QUARTZ (SIO2), which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

QUARTZ (SIO2) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

Country(s) or region

United States & Puerto Rico

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 10-October-2013

Material name: SUPER GEL-X® SDS US

No

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date 19-August-2020

Version # 41

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer CETCO, an MTI Company cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Revision information Disposal considerations: Disposal instructions

Material name: SUPER GEL-X®