

Section 1. Identification

GHS product identifier : BUSAN 1576
 Other means of identification : Biocides
 Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
 See label and/or technical data sheet, if available.

Supplier's details : Buckman Laboratories, Inc.
 1256 North McLean Boulevard
 Memphis, TN 38108
 Phone 1-800-282-5626

Emergency telephone number (with hours of operation) : 24 Hour Emergency Phone 1-800-424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
 ACUTE TOXICITY (dermal) - Category 3
 ACUTE TOXICITY (inhalation) - Category 2
 SKIN CORROSION - Category 1
 SERIOUS EYE DAMAGE - Category 1
 SKIN SENSITIZATION - Category 1
 TOXIC TO REPRODUCTION - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :

Harmful if swallowed.
 Toxic in contact with skin.
 Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 Fatal if inhaled.
 Suspected of damaging fertility or the unborn child.
 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention :

Wear respiratory protection (mist/aerosol). Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Biocides

Product code : BSN1576

Ingredient name	%	CAS number
Diethylene glycol monomethyl ether	>62.148	111-77-3
Methylene bis(thiocyanate)	10.395	6317-18-6
2-(Thiocyanomethylthio)benzothiazole	9.8314	21564-17-0
Fatty acid derived nonionic surfactant	Proprietary	-
Nonionic surfactant	Proprietary	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

While some substances are claimed as trade secret in accordance with the provision of OSHA 29 CFR 1910.1200(i), all known hazards are clearly communicated within this document.

Per Appendix D 1910.1200 OSHA, ranges can be used when there is batch-to-batch variability in a mixture or a trade secret claim.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: - Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
Inhalation	: - Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
Skin contact	: - Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
Ingestion	: - Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.

Notes to physician : Probable mucosal damage may contraindicate the use of gastric lavage.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
 carbon dioxide
 carbon monoxide
 nitrogen oxides
 sulfur oxides
 Cyanide salts are formed when product contacts strong alkali. Thermal decomposition of product can produce toxic vapors of hydrogen cyanide, carbon disulfide and carbon oxisulfide. Contact with fire may generate oxides of sulfur, nitrogen and carbon.

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- Satisfactory Materials of Construction** : Aluminum 6063
 Buna-N Rubber (Nitrile)
 butyl rubber
 C-Flex Tubing Clear
 C-Flex Tubing White
 Dow Silastic Tubing
 EPDM rubber
 MDPE
 Fiberglass-Reinforced Plastic (FRP)
 Hastaloy C-276 Alloy
 Kynar
 Monel Alloy 400
 Nickel Alloy 200
 Norprene Tubing
 Nylon 6-6
 Perfluoroalkoxy (PFA)
 PharMed Tubing
 Polyethylene - Crosslinked (XLPE)
 Polyethylene - High Density (HDPE)
 Polyethylene - Terephthalate (PET)
 Polypropylene (PP)
 Polystyrene (PS)
 PVC Chlorinated (CPVC)
 PVC Flexible
 PVC Rigid
 REHAU Tubing (LDPE)
 Silicone Rubber
 Steel - 304 L Stainless
 Steel - 316 L Stainless
 Steel - Galvanized
 Steel - Mild C-1010
 Steel - Mild C-1020
 Teflon
 Tygon R3400
- NOTE: With respect to all other materials not listed above, user should be aware that use of such materials with this product may be hazardous and result in damages to such materials and other property and personal injuries. No data concerning such materials not listed above should be implied by the user.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eyeface protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If respiratory hazards exist (see section 2), and if use conditions warrant with the potential for airborne exposure existing, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 5.4 [Conc. (% w/w): 0.01%]
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: 95.6°C (204.1°F) [Pensky-Martens]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.

Section 9. Physical and chemical properties

Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.0794
Dispersibility properties	: Dispersible in the following materials: cold water and hot water.
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Will decompose if exposed to high temperature.
Viscosity	: Not available.
VOC	: Not available.

Aerosol product

Section 10. Stability and reactivity

Reactivity	: Reactive screening testing conducted on the active ingredient has resulted in exotherms initiating at temperatures as low as 80°C.
Chemical stability	: Contains 2-(thiocyanomethylthio)benzothiazole. Contains methylene bis(thiocyanate). Do not heat and/or store above 50°C as decomposition may increase packaging pressure and generate toxic vapors.
Possibility of hazardous reactions	: If kept free of contamination and maintained at ambient temperatures during storage and uses, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: strong bases, strong acids oxidizing materials
Hazardous decomposition products	: Cyanide salts are formed when product contacts strong alkali. Thermal decomposition of product can produce toxic vapors of hydrogen cyanide, carbon disulfide and carbon oxisulfide. Contact with fire may generate oxides of sulfur, nitrogen and carbon.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
BUSAN 1576	LC50 Inhalation Dusts and mists	Rat	0.079 mg/l (data based on studies from similar product)	4 hours
	LD50 Dermal	Rat - Female	200 to 2000 mg/kg	-
	LD50 Oral	Rat	466.4 mg/kg	-
Diethylene glycol monomethyl ether Methylene bis(thiocyanate)	LD50 Oral	Mouse	8222 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	7.7 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
2-(Thiocyanomethylthio) benzothiazole	LD50 Oral	Rat	55 mg/kg	-
	LD50 Oral	Rat	81.4 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.067 mg/l	4 hours
	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Dermal	Rat	>5 g/kg	-
	LD50 Oral	Mouse	445 mg/kg	-

Section 11. Toxicological information

Fatty acid derived nonionic surfactant	LD50 Oral LD50 Dermal	Rat Rabbit	750 mg/kg 8000 mg/kg	- -
Nonionic surfactant	LD50 Oral LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rat Rat Rabbit Rat	>5000 mg/kg 147 mg/m ³ >20 g/kg 5 g/kg	- 4 hours - -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
BUSAN 1576	Skin - Primary dermal irritation index (PDII)	Rabbit	4.9	30 to 60 minutes	-
Diethylene glycol monomethyl ether	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
2-(Thiocyanomethylthio) benzothiazole	Eyes - Moderate irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 mg	-
Nonionic surfactant	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Skin - Primary dermal irritation index (PDII)	Rabbit	7.4	-	-
Nonionic surfactant	Eyes - Severe irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Methylene bis(thiocyanate)	skin	Guinea pig	Sensitizing
2-(Thiocyanomethylthio) benzothiazole	skin	Guinea pig	Sensitizing
Fatty acid derived nonionic surfactant	skin	Guinea pig	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

This product has not been tested unless noted in summary results.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Nonionic surfactant	Category 1	inhalation	-

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact : Causes serious eye damage.
- Inhalation : Fatal if inhaled.
- Skin contact : Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.

Section 11. Toxicological information

Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
BUSAN 1576	466.4	200	N/A	0.88	0.079
methylene dithiocyanate	55	2500	N/A	N/A	0.0077
(benzothiazol-2-ylthio)methyl thiocyanate	750	N/A	N/A	N/A	0.067
Fatty acid derived nonionic surfactant	N/A	8000	N/A	N/A	N/A
Nonionic surfactant	5000	N/A	N/A	0.147	N/A

Section 12. Ecological information








Toxicity

Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN2922	UN2922	UN2922
UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S. (2-(Thiocyanomethylthio) benzothiazole, Methylene bis (thiocyanate))	CORROSIVE LIQUID, TOXIC, N.O.S. (2-(Thiocyanomethylthio) benzothiazole, Methylene bis (thiocyanate)). Marine pollutant (Methylene bis(thiocyanate), 2-(Thiocyanomethylthio) benzothiazole)	CORROSIVE LIQUID, TOXIC, N.O.S. (2-(Thiocyanomethylthio) benzothiazole, Methylene bis (thiocyanate))
Transport hazard class(es)	8 (6.1)  	8 (6.1)   	8 (6.1)  
Packing group	III	III	III
Environmental hazards	No.	Yes.	No.
Additional information	Remarks ERG Guide 154	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-A, S-B IMDG Code Segregation group SGG6 - Cyanides Remarks ERG Guide 154, HazMat Code 4936015	The environmentally hazardous substance mark may appear if required by other transportation regulations. Remarks ERG Guide 154, ERG Code 8P

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

Potential impurities present in trace quantities are included in the regulatory listings of this section.

U.S. Federal regulations : **United States inventory (TSCA 8b)**: This product is subject to regulation under the US Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) and is therefore exempt from US Toxic Substances Control Act (TSCA) Inventory listing requirements.

Clean Water Act (CWA) 307: Anionic surfactant; dimethylnitrosoamine

Clean Water Act (CWA) 311: Anionic surfactant; di-Methylamine, gas; propylene oxide; acetaldehyde

SARA 302/304

Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
Ethylene oxide	<0.0056525	Yes.	1000	-	10	-
Propylene oxide	<0.005	Yes.	10000	1444.3	100	14.4
N-nitrosodimethylamine	0.00000025	Yes.	1000	118.7	10	1.2

SARA 304 RQ : 196571.1 lbs / 89243.3 kg [21841.4 gal / 82678.6 L]

SARA 311/312

Classification : ACUTE TOXICITY (oral) - Category 4
 ACUTE TOXICITY (dermal) - Category 3
 ACUTE TOXICITY (inhalation) - Category 2
 SKIN CORROSION - Category 1
 SERIOUS EYE DAMAGE - Category 1
 SKIN SENSITIZATION - Category 1
 TOXIC TO REPRODUCTION - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Composition/information on ingredients

Name	%	Classification
Diethylene glycol monomethyl ether	>62.148	FLAMMABLE LIQUIDS - Category 4 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2
Methylene bis(thiocyanate)	10.395	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (inhalation) - Category 1 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1
2-(Thiocyanomethylthio) benzothiazole	9.8314	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Fatty acid derived nonionic surfactant	Proprietary	SKIN SENSITIZATION - Category 1
Nonionic surfactant	Proprietary	ACUTE TOXICITY (inhalation) - Category 1 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Diethylene glycol monomethyl ether	111-77-3	>62.148
Supplier notification	Diethylene glycol monomethyl ether	111-77-3	>62.148

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Section 15. Regulatory information

- CERCLA** : CERCLA: Hazardous substances.: Anionic surfactant: 1000 lbs. (454 kg); dimethylnitrosoamine: 10 lbs. (4.54 kg); di-Methylamine, gas: 1000 lbs. (454 kg); ethylene oxide: 10 lbs. (4.54 kg); propylene oxide: 100 lbs. (45.4 kg); acetaldehyde: 1000 lbs. (454 kg); ethanediol: 5000 lbs. (2270 kg); 2-methoxyethanol: No RQ is being assigned to the generic or broad class.; 2-(2-methoxyethoxy)ethanol: No RQ is being assigned to the generic or broad class.; 2-ethoxyethanol: 1000 lbs. (454 kg); methanol: 5000 lbs. (2270 kg); 1,4-dioxane: 100 lbs. (45.4 kg);
- FDA** : This product is allowed under the following FDA (21 CFR) sections :176.300 Limitation: Must be added prior to or during the sheet-forming process.
- EPA Reg. No.** : 1448-443
- FIFRA** : This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

Corrosive. Causes irreversible eye damage and skin burns. May be fatal if inhaled. May be fatal if swallowed or absorbed through skin. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wear goggles or face shield. Wear coveralls over long-sleeved shirt and long pants; socks and chemical resistant footwear; chemical-resistant gloves such as barrier laminate, butyl rubber, nitrile rubber, neoprene rubber, polyvinyl chloride or viton; and respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C); or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G); or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with an R, P, or HE prefilter. In addition to the PPE listed above, mixers, loaders, and cleaners of equipment must also wear chemical-resistant apron. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

User Safety Requirements: Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

User Safety Recommendation: User should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. User should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Handlers participating in hand-dip applications, including introduction of materials to and removal from the dip and handling materials still wet from the dip, must wear chemical-resistant full front aprons with attached full-sleeve gloves.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

Section 15. Regulatory information



State regulations

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including 2-Mercaptobenzothiazole, Propylene oxide, acetaldehyde, 1,4-Dioxane and N-Nitrosodimethylamine, which are known to the State of California to cause cancer, and Ethylene Glycol, Ethylene glycol monomethyl ether, Ethylene glycol monoethyl ether and Methanol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Ethylene Glycol	-	Yes.
Ethylene glycol monomethyl ether	-	Yes.
Ethylene glycol monoethyl ether	-	Yes.
Methanol	-	Yes.
2-Mercaptobenzothiazole	-	-
Ethylene oxide	Yes.	Yes.
Propylene oxide	-	-
acetaldehyde	Yes.	-
1,4-Dioxane	Yes.	-
N-Nitrosodimethylamine	Yes.	-

Section 16. Other information


Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



History

Date of printing : Aug 10, 2022
 Date of issue / Date of revision : Aug 10, 2022
 Date of previous issue : Aug 10, 2022
 Version : 0.25
 Prepared by : Buckman Regulatory Affairs

Section 16. Other information

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 UN = United Nations

☑ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Buckman Laboratories, Inc. warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use outside of such directions.

Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE**. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty.

The exclusive remedy against seller shall be in a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort.

Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the commercial arbitration rules of the American Arbitration Association, and judgment upon the rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

Buckman expressly disclaims responsibility, thus any liability, for the creation, accuracy, or completeness of the labeling and Safety Data Sheet (SDS) required for our customer's product under the Occupational Health and Safety Administration's Hazard Communication Standard, 29 C.F.R. §1910.1200 (2012). While our customers should take all necessary steps to ensure that an appropriate label and SDS is generated for their product and provided to all downstream users in accordance with the Hazard Communication Standard, customers may use information from Buckman's label and SDS for their product as a starting point for developing its own GHS-compliant label and SDS. Customer agrees to indemnify and hold Buckman harmless from any claims, causes of actions, fines, or damages sought by a local, state, or federal government, or agency, including its reasonable attorney fees, should Customer violate any OSHA laws or any other federal or state laws in using or selling this product.